



# LIQUID TAPE

~ ELECTRICAL ~

BRUSH-ON INSULATION

## DESCRIPTION:

LIQUID TAPE is an air dry synthetic rubber coating that can be easily brushed on and exhibits excellent moisture, acid, alkaline, abrasion and dielectric resistance. LIQUID TAPE, available in red, black, green, and white, will not crack, peel, or harden and remains flexible – even under extreme conditions. LIQUID TAPE can be used in many applications including electrical connections for boats, trailers, RV's, trucks, automobiles, timers, pool electicals, bilge pumps, sprinkler pumps, instruments, computers, circuit boards, switches, and will stop terminal screws from vibrating loose. Use LIQUID TAPE to insulate, protect and color code.

## SPECIFICATIONS:

Dielectric: (ASTM D -149) 1,400 v/mil  
Solids (wt.): 24 %  
Tensile: (ASTM D -638) 3,740 psi  
Elongation: (ASTM D -638) 430%  
Cut resistance: (ASTM D -1044) very good  
Shelf life: 1 + years at 77°F unopened container  
Chemical resistance:  
    acids, alkalines, pollutants - excellent  
    petroleums - limited

Durometer shore A: (ASTM D -2240) 70  
Salt spray: (ASTM B -117) passed 1,000 hours  
Weather ability: (ASTM G -53) 3-5 years  
Temperature use range: -30°F to 200°F.  
Stone abrasion: (ASTM D-3170) excellent  
Permeability: (ASTM E -96) .03 grains/sq. ft./hr.  
Viscosity range: 90 – 110 K.U. @ 77°F (+/- 2°F)

## SURFACE PREPARATION:

Wires, terminals or all other surfaces must be clean, dry, and free of all oils, grease, wax and loose rust.

## MIX WELL BEFORE USE. USE ADEQUATE VENTILATION.

Stir gently with brush applicator cap to avoid producing bubbles before each use. Apply wet overlapping coats. Allow 10 - 20 minutes dry time (dry to the touch) before applying additional coats to desired thickness. A minimum of 2 -3 coats are recommended for best results. Allow 24 hours to fully cure.

CAUTION: Turn off power before starting electrical work and follow your local electrical codes. Minimal 2 coats required (5+ mils) to assure good dielectric protection.

## HINTS:

**Allow 4 hours dry time per coat before use.** Allow overnight drying whenever possible. Avoid excessive air movement, heat or humidity. Always use proper ventilation and protection.



Plasti Dip International  
3920 Pheasant Ridge Drive  
Blaine, MN 55449  
Phone: 800-969-5432  
Fax: 763-785-2058



# **ADDITIONAL APPLICATION IDEAS**

**Landscape Lighting  
Cables  
Electronics  
Gauges  
Outlet boxes  
Sensors  
Circuit Boards  
Underground wiring  
Controls  
Valves / Actuators  
Alarms / Sirens  
Distributors  
Junction boxes  
Sleeves for LEDS  
Robot electronics**

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the applications of this information or the safety and suitability of our products, either alone or in combination with other product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products whether used alone or in combination with other products. Ever changing V.O.C. regulations in your area may require you to contact local authorities for proper use and/or disposal of this product. Should you need further assistance, please contact PLASTI DIP INTERNATIONAL technical service.

Performix and logo are registered trademarks of PLASTI DIP INTERNATIONAL