




Allied

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT IDENTIFICATION AND USE

PRODUCT IDENTIFIER : DIP SEALANT			<p>0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe</p> <p>HEALTH HAZARD: 1 FIRE HAZARD: 0 REACTIVITY: 0 PROTECTIVE EQUIPMENT: C</p>  <p>Safety Glasses</p>  <p>Gloves</p>  <p>Protective Apron</p> <p>DO NOT BREATHE VAPORS. DO NOT GET IN EYES, SKIN. DO NOT GET ON CLOTHING. DO NOT INGEST</p>
MANUFACTURER'S NAME: ALLIED			
STREET ADDRESS 2040 LEE STREET, HOLLYWOOD, FLORIDA, 33020, USA			
OFFICE TELEPHONE: 800-327-8487	FAX: 954-923-6462	24 HR. EMERGENCY TELEPHONE 800-424-9300 CHEMTREC	
THIS IS A CHEMICAL PRODUCT. ALL CHEMICAL PRODUCTS POSE AN INHERENT HEALTH RISK. BEFORE USE ALWAYS READ COMPLETE LABEL AND MSDS FOR SAFE HANDLING PROCEDURES			

SECTION 2 – INGREDIENT INFORMATION

INGREDIENTS	%	CAS NUMBER	HAZARD DATA
<i>*These ingredients are subject to the reporting requirements of SARA 313 and 40 CFR 372</i>			
Aqueous blend of polymeric materials, cross linking agents and gloss promoters – No listed hazardous ingredients.			
ALL INGREDIENTS ARE LISTED IN THE US TOXIC SUBSTANCE CONTROL ACT (TSCA)			

SECTION 3 - PHYSICAL DATA

PHYSICAL STATE LIQUID	ODOR AND APPEARANCE Clear liquid, Negligible odor	WATER SOLUBILITY Soluble	PH 11	SPECIFIC GRAVITY 1.01
VAPOR PRESSURE (MM Hg) < 3.0 @ 20°C	VAPOR DENSITY (AIR=1) >1	EVAPORATION RATE (Butyl acetate = 1) <1	BOILING POINT (°F) 212	V.O.C.'s 0 %

SECTION 4 - FIRE AND EXPLOSION DATA

FLAMMABILITY YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	IF YES, UNDER WHICH CONDITIONS? * Not applicable			
EXTINGUISHING MEDIA Not applicable.		SPECIAL FIRE FIGHTING PROCEDURES: Use self contained breathing apparatus if needed.		
FLASHPOINT (°F) AND METHOD None		UPPER FLAMMABLE LIMIT (% BY VOLUME) : Unknown	LOWER FLAMMABLE LIMIT (% BY VOLUME): Unknown	
AUTOIGNITION TEMPERATURE (°C) Not Known	HAZARDOUS COMBUSTION PRODUCTS Oxides of carbon and hydrocarbons.			
EXPLOSION DATA * NOT KNOWN	SENSITIVITY TO IMPACT NO	SENSITIVITY TO STATIC DISCHARGE NO		

SECTION 5 - REACTIVITY DATA

CHEMICAL STABILITY YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION None		
INCOMPATIBILITY WITH OTHER SUBSTANCES Strong oxidizing agents, strong reducing agents, strong acids			
HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide and hydrocarbons		This product is not photochemically reactive	

Allied

MATERIAL SAFETY DATA SHEET

PRODUCT IDENTIFIER * **DIP SEALANT**

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY SKIN CONTACT ■ SKIN ABSORPTION □ EYE CONTACT ■ INHALATION ■ INGESTION ■

ACUTE EXPOSURE TO PRODUCT: Inhalation – Excessive inhalation can cause irritation of the respiratory tract, signs of central nervous system depression, dizziness nausea and headache. Eye - Will cause severe irritation, burning, redness and tearing. Skin - Can cause irritation, redness burning and drying. Ingestion causes irritation of the digestive tract.

CHRONIC EXPOSURE TO PRODUCT: Prolonged skin contact may aggravate an existing dermatitis.

CARCINOGENICITY: No ingredient is listed as carcinogenic or potentially carcinogenic by IARC, NTP or OSHA.

TARGET ORGAN EFFECTS: - Skin, eyes – possible irritation

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with running water for at least 15 minutes. Seek medical attention.

SKIN: wash affected area with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical attention.

INGESTION: Do not induce vomiting. Material is an aspiration hazard, may enter lungs and cause lung damage. Seek immediate medical attention.

SECTION 7 - PREVENTATIVE MEASURES

GLOVES Nitrile for incidental, non-immersion contact.	RESPIRATOR: Use NIOSH approved SCBA in emergency situations or confined areas.	EYE (SPECIFY) Splash proof goggles or face shield
---	---	---

CLOTHING: Boots, aprons, or chemical suits should be used when necessary to prevent skin contact.

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) : Use local exhaust or dilution ventilation as appropriate to control exposure below permissible levels. Vapors are heavier than air and will collect in low areas

LEAK AND SPILL PROCEDURE: Provide maximum ventilation. Dike area to contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.

WASTE DISPOSAL: Contaminated vermiculite or porous surface must be disposed of in a permitted hazardous waste facility. Recovered liquids may be reprocessed or incinerated in a permitted hazardous waste facility. In all cases material should be disposed of in accordance with all applicable regulations.

HANDLING PROCEDURES AND EQUIPMENT: Keep container closed when not in use. Store only in closed, properly labeled containers. Store in a cool, dry, well ventilated area away from heat sparks and open flames. Treat empty containers as containing product residues.

SECTION 8 - ADDITIONAL INFORMATION

CALIFORNIA PROPOSITION 65: *This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness.*

This product contains the following chemicals known by the state of California to cause cancer: None

This product contains the following chemicals known by the state of California to cause reproductive harm : None

SHIPPING INFORMATION: Not regulated for shipping purposes

SECTION 9 - PREPARATION AND DATE OF MSDS

PREPARED BY (GROUP DEPARTMENT, ETC.) TECHNICAL SERVICES DEPARTMENT	PHONE NUMBER 1-800-327-8487	DATE June 2014
---	--------------------------------	-------------------

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume risk of his use thereof.