

SAFETY DATA SHEET

PLASTIDIP

Page: 1

Compilation date: 31/05/2012

Revision date: 18/01/2016

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PLASTIDIP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Plasti Dip

East Meon

Petersfield

Hampshire

GU32 1QR

UK

Tel: +44 (0) 1730 823 123

Email: sales@plastidip.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1730 823 823 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Acute Tox. 4: H312+332; Flam. Liq. 3: H226; -: EUH066

Most important adverse effects: Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P260: Do not breathe vapours.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P362: Take off contaminated clothing.
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE - REACH registered number(s): 01-2119488216-32

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	50-70%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove from exposure, rest and keep warm. In severe cases, or if recovery is not rapid or complete, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

DNEL/PNEC Values

Hazardous ingredients:

XYLENE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	442 mg/m ³	Workers	Local
DNEL	Inhalation	180 mg/kg/day	Workers	Systemic
DNEL	Dermal	3182 mg/kg/day	Workers	Systemic
PNEC	Fresh water	0.327 mg/l	-	-
PNEC	Fresh water sediments	12.46 mg/kg	-	-
PNEC	Marine sediments	12.46 mg/kg	-	-
PNEC	Soil (agricultural)	2.31 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves, change regularly to avoid permeation problems.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Colourless
Odour: Aromatic
Evaporation rate: No data available.
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Insoluble
Viscosity: No data available.
Boiling point/range°C: 136-200
Melting point/range°C: No data available.
Flammability limits %: lower: 0.6
upper: 8.0
Flash point°C: 23 - 55
Part.coeff. n-octanol/water: No data available.
Autoflammability°C: >230
Vapour pressure: No data available.
Relative density: 0.830
pH: No data available.
VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 6

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

[cont...]

SAFETY DATA SHEET

PLASTIDIP

Page: 7

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

H332: Harmful if inhaled.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.