

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 1

Compilation date: 01/09/2016

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

**Product code:** PLASTIDIP

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, primers.

### 1.3. Details of the supplier of the safety data sheet

# ' * #	3ODVWL'LS8.
\$\$	(DVW0HRQ3HWHUVILHOG
	+DPSVKLUH
	8458.
( ' "	
+ )\$	SODVWLGLSFRXN
!# (	VDOHVSODVWLGLSFRXN
# , * ' " # )	

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1759 304676 (Office Hours Only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** STOT SE 3: H335; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Aer. Sol. 1: H222; Skin Irrit. 2: H315; -: H229

**Most important adverse effects:** Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

**Label elements:**

**Hazard statements:** H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H315: Causes skin irritation

H319: Causes serious eye irritation

H335: May cause respiratory irritation

H411: Toxic to aquatic life with long lasting effects

**Hazard pictograms:** GHS02: Flam

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 2

GHS07: Exclamation mark

GHS09: Environmental



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

## 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not classified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### PETROLEUM GASES, LIQUEFIED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit	Flam. Gas 1: H220; Pr. Gas: H280	30-50%

##### LIGHT ALIPHATIC NAPHTHA (VM&P NAPHTHA)

-	64742-89-8	-	Skin Irrit. 2: H315; Asp. Tox. 1: H304; Eye Irrit. 2: H319; STOT SE 3: H335; Flam. Liq. 2: H225; -: EUH018	10-30%
---	------------	---	--	--------

##### HEPTANE C - REACH registered number(s): 01-2119475515-33

205-563-8	142-82-5	-	Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 1: H410	10-30%
-----------	----------	---	--	--------

##### XYLENE - REACH registered number(s): 01-2119484661-33-0004

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 3

## ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	---	-------

## HEPTAN-2-ONE

203-767-1	110-43-0	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H302	1-10%
-----------	----------	---	---	-------

## ETHYLBENZENE

202-849-4	100-41-4	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; STOT RE 2: H373; Asp. Tox. 1: H304	1-10%
-----------	----------	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Consult a doctor.
- Inhalation:** Move to fresh air in case of accidental inhalation of vapours.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** No data available.
- Eye contact:** No data available.
- Ingestion:** No data available.
- Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. For explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 4

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**PETROLEUM GASES, LIQUEFIED**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1,750mg/m <sup>3</sup>	2,180mg/m <sup>3</sup>	-	-

**XYLENE**

UK	-	-	220mg/m <sup>3</sup>	441mg/m <sup>3</sup>
----	---	---	----------------------	----------------------

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 5

## ETHYL METHYL KETONE

UK	600 mg/m <sup>3</sup>	899 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## HEPTAN-2-ONE

UK	237 mg/m <sup>3</sup>	475 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## ETHYLBENZENE

UK	441 mg/m <sup>3</sup>	552 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## DNEL/PNEC Values

### Hazardous ingredients:

#### HEPTANE C

Type	Exposure	Value	Population	Effect
DNEL	Oral	149mg/kg bww/day	Consumers	Systemic
DNEL	Dermal	149mg/kg bw/day	Consumers	Systemic
DNEL	Dermal	300mg/kg bw/day	Workers	Systemic

#### XYLENE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	289mg/m <sup>3</sup>	Workers	Systemic
DNEL	Dermal	180mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	77mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation	174mg/m <sup>3</sup>	Consumers	Systemic
DNEL	Dermal	108mg/kg/day	Consumers	Systemic
DNEL	Inhalation	14.8mg/m <sup>3</sup>	Consumers	Systemic

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Chemically resistant gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** Various

**Odour:** Characteristic odour

**Flash point°C:** -60

**VOC g/l:** 87.29%

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 6

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### LIGHT ALIPHATIC NAPHTHA (VM&P NAPHTHA)

VAPOURS	RAT	4H LC50	3400	ppmV
---------	-----	---------	------	------

#### HEPTANE C

DERMAL	RBT	LD50	>2000	mg/kg
DUST/MIST	RAT	4H LC50	>5	mg/l
ORAL	RAT	LD50	>2000	mg/kg

#### XYLENE

DERMAL	RBT	LD50	>1700	mg/kg
GASES	MUS	1H LC50	5000	ppmV
ORAL	RAT	LD50	4300	mg/kg

[cont...]

## SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 7

### HEPTAN-2-ONE

IPR	RAT	LD50	800	g/kg
ORL	MUS	LD50	730	g/kg
ORL	RAT	LD50	1670	g/kg

### ETHYLBENZENE

IPR	MUS	LD50	2624	µl/kg
ORL	RAT	LD50	3500	g/kg

#### Relevant hazards for product:

Haz	Rout	Bas
Skin cor on/irri	DRM	Haz dous: calculated
Serious eye d age/i	OPT	Haz dous: calculated
STOT-single exposur	INH	Haz dous: calculated

#### Symptoms / routes of exposure

**Skin contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

**Inhalation:** No data available.

**Delayed / immediate effects:** No data available.

**Other information:** Not applicable.

### Section 12: Ecological information

#### 12.1. Toxicity

##### Hazardous ingredients:

##### XYLENE

Daph a m	48H EC50	<10	g/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	41	g/l

#### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

#### 12.4. Mobility in soil

**Mobility:** No data available.

[cont...]

# SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 8

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic or .

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Not applicable.

**Disposal of packaging:** Not applicable.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

### 14.2. UN proper shipping name

**Shipping name:** AEROSOLS

### 14.3. Transport hazard class(es)

**Transport class:** 2

### 14.4. Packing group

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]



## SAFETY DATA SHEET

PLASTI DIP SPRAY ALL COLOURS INCLUDING BLAZE CAMO SDS-EN

Page: 9

### Section 16: Other information

#### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

**Phrases used in s.2 and s.3:** EUH018: In use may form <flammable/explosive> vapour-air mixture.

EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour

H226: Flammable liquid and vapour

H229: Pressurised container: May burst if heated

H302: Harmful if swallowed

H304: May be fatal if swallowed and enters airways

H312: Harmful in contact with skin

H315: Causes skin irritation

H319: Causes serious eye irritation

H332: Harmful if inhaled

H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

H373: May cause damage to organs <or sensitive organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the damage>.

H410: Very toxic to aquatic life with long lasting effects

H411: Toxic to aquatic life with long lasting effects

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information supplied by LMA is only considered accurate at the time of its creation. During this time the classifications of substances may change. Therefore it is possible that current work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.

